

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




FIG. 1





FIG. 2



DESCRIPTION [TAB] THIS IS A DESCRIPTION [CR] [LF]
CLAIM [TAB] THIS IS A CLAIM [CR] [LF]

FIG. 3





FIG. 5

PatIntelligence P-Shoe - Dell (General)
File Document View Tools Help

Back Open Save Clip Print Shoe View File Order Using Doc Select Exclude

5,946,469	Computer sys
5,852,739	Low profile p
5,831,821	Computer ha
5,815,351	Overload pro
5,808,663	Multimedia c
5,804,875	Computer sys
5,782,354	Corrugated e
5,777,843	Power supply
5,768,099	Computer wit
5,754,397	Docking con
5,647,748	Printed circui
5,625,534	Portable com
5,623,869	Laptop table
5,497,292	Configurable
4,999,767	System havin



Power supply mounting assembly for electronic equipment

A mounting assembly for mounting a component in electronic equipment, such as a computer system, which includes an enclosure and a mounting bracket pivotally mounted to the enclosure. One or more retaining members are disposed on the bracket for engaging the component to retain the component in the bracket in abutting relationship. The bracket, and therefore the component, are connected to the enclosure so that they can be pivoted between a position in which the component is mounted in the enclosure and a position in which it extends out of the enclosure. In the mounted position, the bracket forms a portion of

☒ Undecided
☒ Selected
☒ Excluded

Document 8 of 15: 0 selected, 0 excluded, 100% undecided.
JP Shoe 5/15/2016

FIG. 6

008F0F520F6560




FIG. 7

008101-5206960

PatIntelligence P-Shoe - Dell (General)

Document View Tools Help

Open Save Print Find Copy Paste Undo Redo

5,946,469	Computer sy
5,852,739	Low profile p
5,831,821	Computer he
5,815,351	Overload pro
5,809,663	Multimedia c
5,804,875	Computer sy
5,782,354	Corrugated e
5,777,848	Power suppl
5,768,099	Computer wi
5,754,397	Docking cor
5,647,748	Printed circ
5,625,534	Portable cor
5,623,869	Laptop table
5,497,292	Configurable
4,999,767	System hav

☐ Understood
☒ Selected
☒ Excluded

Abstract Bibliographic Claims Notes

Document 5 of 15 0 selected, 0 excluded, 100% understood

Sheet 15 of 219

Multimedia carousel for video conferencing and multimedia presentation applications

A multimedia carousel for use in video conferencing and multimedia presentation applications is disclosed. The multimedia carousel includes a cube-shaped media unit rotatably disposed on a stationary base. Each of the four outward-facing sides of the media unit is equipped with an active color matrix display, a voice-activated charge coupled device ("CCD") camera and a microphone. A single high-fidelity speaker is disposed on the

FIG. 8

Patent Intelligence
P-Sheet - Bell (General)

Open
Save
Copy
Print
Shrink
Grow
Rotate
Undo
Redo
Delete
Find

5,946,469	Computer sy
5,852,739	Low profile p
5,831,821	Computer ha
5,815,351	Overload pro
5,808,883	Multimedia c
5,804,875	Computer sy
5,782,354	Corrugated c
5,777,848	Power suppl
5,768,099	Computer wi
5,754,397	Docking con
5,647,748	Printed circ
5,625,534	Portable con
5,623,869	Laptop table
5,497,292	Configurable
4,999,767	System hav

☐ Undecided
☒ Selected
☐ Excluded

Abstract
Bibliographic
Claims
Notes

7 Pages, 25 Claims, 4 Figures.

Multimedia carousel for video conferencing and multimedia presentation applications

A multimedia carousel for use in video conferencing and multimedia presentation applications is disclosed. The multimedia carousel includes a cube-shaped media unit rotatably disposed on a stationary base. Each of the four outwardly facing sides of the media unit is equipped with an active color matrix display, a voice-activated charge coupled device ("CCD") camera and a microphone. A single high fidelity speaker is disposed on the top side surface of the cube for producing high quality audio output.

FIG. 9



83

A multimedia carousel for use in video conferencing and multimedia presentation applications is disclosed. The multimedia carousel includes a cube-shaped media unit, rotatably disposed on a stationary base. Each of the four outwardly facing sides of the media unit is equipped with an active color matrix display, a voice-activated

Abstract / Bibliographic / Date / Name

Document 5 of 16: 0 selected, 0 excluded, 100% indexed

PG 1051218

FIG. 10

008701-54016960

PatIntelligence P-Shoe - Dell (General)
Document View Tools Help

Back Open Save Cut Print P-Shoe View Links Other Laptop Doc Select

5,946,463	Computer sys
5,852,739	Low profile p
5,831,821	Computer ho
5,815,351	Overload pro
5,808,663	Multimedia c
5,804,875	Computer sys
5,782,354	Corrugated e
5,777,813	Power supply
5,768,099	Computer wi
5,754,397	Docking con
5,647,748	Printed circ
5,625,534	Portable com
5,623,869	Laptop table
5,497,292	Configurable
4,999,767	System havin

Power supply mounting assembly for electronic equipment

A mounting assembly for mounting a component in electronic equipment, such as a computer system, which includes an enclosure and a mounting bracket pivotally mounted to the enclosure. One or more retaining members are disposed on the bracket for engaging the component to retain the component in the bracket in abutting relationship. The bracket, and therefore the component, are connected to the enclosure so that they can be pivoted between a position in which the component is mounted in the enclosure and a position in which it extends out of the enclosure. In the mounted position, the bracket forms a portion of one or more walls of the enclosure.

7 Pages, 21 Claims, 5 Figures.


SERIAL: 08/771,012

Abstract Bibliographic Claims Notes

Document 8 of 15 0 selected 0 excluded 100% undecided

18916-5316/218


FIG. 12



000001 52016560

FIG.

14






Fig 15




Fig 16

000001-92016900





Fig. 17

71.50



-

An amusement ride includes a vehicle traveling down a chute through a region of water. The vehicle is shaped to minimize splashing and to allow water to flow away from the vehicle. The vehicle flanks are curved to deflect splashing water down and away from the vehicle, and the vehicle bow has upper flanks to deflect water down and away from the vehicle. The vehicle bottom has a concave channel to accommodate water displaced by the vehicle. The vehicle has sets of wheels for traveling, for guiding lateral motion, and for interacting with floating prevention mechanism. A groove along each side of the vehicle accommodates a splash prevention member on the water chute.

11 Pages, 16 Claims, 10 Figures.

SEVAL: 00290,000

ALLIANCE June 27, 1995

PPOBPH: September 2, 1982, Axx. No.
 4-224983

ISSUE DATE: March 25, 1987

INVENTOR: Ariga, Manishi; Yokohama Japan(JPX)
Ojima, Reichi; Hachioji, Japan(JPX)
Kawachi, Yoshihiro; Tokyo
Japan(JPX)
Kobayashi, Toshihiro; Fujisawa
Japan(JPX)